

Alfa Laval Semi-welded MA30

Gasketed plate heat exchanger for demanding applications

Introduction

Alfa Laval Industrial semi-welded line is used when gaskets are not suitable for one of the process media. The semi-welded line can also withstand a higher design pressure compared to fully gasketed plate-and-frame heat exchangers.

Suitable for a wide range applications, this model is available with a large selection of plate and gasket types.

Applications

- Chemicals
- Energy and Utilities
- HVAC and Refrigeration
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Steel
- Water and Waste treatment

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features


Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:







- Five-point alignment
- · Reinforced hanger
- Chocolate pattern distribution area
- Glued gasket
- Leak chamber
- RefTightTM sealing system
- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining



- Lock washer
- Pressure plate roller
- Tightening bolt cover
- Optimized Alfa Laval drain connection

Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, integrity testing, monitoring and much more.


For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.


General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

Dimensional drawing

Measurements mm (inches)





Frame type	Н	W	h
WFG	2940 (115.7")	1170 (46.1")	521 (20.5")
WFD	2940 (115.7")	1170 (46.1")	521 (20.5")
WF	2940 (115.7")	1170 (46.1")	521 (20.5")

Technical data

Plates	Туре	Free channel, mm (inches)
MA30-W	Semi-welded	4.0 (0.16)

Materials	
	304/304L, 316/316L, 904L, 254
Heat transfer plates	C-276, C-2000, D-205
	Ti, TiPd
Field gaskets	NBR, EPDM
Ring gaskets	NBR, EPDM, FKM, HeatSeal, PTFE, CR
Flange connections	Carbon steel
rialige confilections	Metal lined: stainless steel, titanium
Frame and pressure plate	Carbon steel, epoxy painted

Other materials may be available on request

Operational data

Frame type	Max. design pressure	Max. design
rraine type	(barg/psig)	temperature (°C/°F)
FG, ASME	10.3/150	177/350
FG, PED	16.0/232	180/356
FGR, PED	16.0/232	200/392
FD, ASME	20.7/300	177/350
FD, PED	25.0/362	180/356
FDR, PED	25.0/362	180/356
FS, ASME	27.6/400	160/320
FS, PED	30.0/435	160/320

Extended pressure and temperature rating may be available on request.

Flange connections

Frame type	Connection standard	
FG. ASME	ASME B16.5 Class 150 NPS 12	
FG, ASIVIE	ASME B16.5 Class 150 NPS 14	
	EN 1092-1 DN300 PN16	
FO DED	EN 1092-1 DN350 PN16	
FG, PED	ASME B16.5 Class 150 NPS 12	
	ASME B16.5 Class 150 NPS 14	
	EN 1092-1 DN300 PN16	
FGR, PED	EN 1092-1 DN350 PN16	
FGR, PED	ASME B16.5 Class 150 NPS 12	
	ASME B16.5 Class 150 NPS 14	
ED ACME	ASME B16.5 Class 300 NPS 12	
FD, ASME	ASME B16.5 Class 300 NPS 14	
FDc, ASME		
	EN 1092-1 DN300 PN25	
FD, PED	EN 1092-1 DN350 PN25	
FD, PED	ASME B16.5 Class 300 NPS 12	
	ASME B16.5 Class 300 NPS 14	
	EN 1092-1 DN300 PN25	
	EN 1092-1 DN350 PN25	
FDR, PED	ASME B16.5 Class 300 NPS 12	
	ASME B16.5 Class 300 NPS 14	
EC ACME	ASME B16.5 Class 400 NPS 12	
FS, ASME	ASME B16.5 Class 400 NPS 14	
	EN 1092-1 DN300 PN40	
FO DED	EN 1092-1 DN350 PN40	
FS, PED	ASME B16.5 Class 400 NPS 12	
	ASME B16.5 Class 400 NPS 14	

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T 9115.

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE00116-3-EN-GB © Alfa Laval Corporate AB